



(Formerly known as Asha Resins Private Limited)

ASHAFLOC - A95

Anionic Polyelectrolyte

DESCRIPTION

ASHAFLOC - A95 is an anionic, high molecular weight performance coagulant with dual-purpose functionality. It can also serve as a filter aid, especially where most conventional filter aids are ineffective.

ASHAFLOC - A95 is effective in a wide range of solid-liquid separations, including:

- Effluent water treatment.
- Removal of suspended particles from raw water.
- Treatment of oil-water emulsions.
- Low-turbidity water applications.

In most cases, it can be used independently or in combination with alum. For enhanced water quality, its use with inorganic flocculants is recommended.

Recommended Dosage:

- Coagulation Aid: 0.25 ppm to 5 ppm.
- Filtration Aid: 10 ppm to 30 ppm.

SPECIFICATIONS

Parameter	Specification
Appearance	Highly viscous pourable liquid
Solubility	Fully water-soluble
Viscosity (1%)	80 - 200 cps
Specific Gravity (0.2%)	1.01 – 1.06
рН	8.5 - 10.0
Nature	Highly anionic

Regd. Office: Gat No 227/2, Village Dhanore, 020-2638 2401 Tel:

& Factory. Alandi-Markal Road, Tal. Khed E-mail: office@asharesins.com

Dist. Pune - 412 105

Website: www.asharesins.com CIN No: U99999MH1993PLC073569 GSTIN: 27AABCA5790M1Z9





DOSAGE

The required dosage depends on the solid content in the system to be treated:

- Coagulation Aid: 0.25 to 1.0 ppm.
- Filter Aid: 1 to 5 ppm.

FEEDING

- Prepare a 0.2% solution in water.
- Ensure all solid particles are fully dissolved and no clumps ("fish eyes")
- Dosing is recommended at the system's inlet using a metering pump.

HANDLING PRECAUTIONS

- **Safety:** Generally safe for handling.
- Avoid contact with eyes and prolonged skin exposure.

PACKAGING

ASHAFLOC - A95 is available in 35 kg and 50 kg HDPE containers.

NOTE

The specifications provided are indicative and subject to change without prior notice based on application needs.

These suggestions and data are based on information we consider reliable and are offered in good faith. However, no guarantees are made, as conditions and methods of use are beyond our control. Prospective users are advised to assess the material's suitability for their specific applications before commercial adoption.

For additional information, product samples, Material Safety Data Sheets (MSDS), or technical support, please contact us.

Regd. Office: Gat No 227/2, Village Dhanore, 020-2638 2401 Tel:

& Factory. Alandi-Markal Road, Tal. Khed E-mail: office@asharesins.com

Dist. Pune - 412 105

Website: www.asharesins.com CIN No: U99999MH1993PLC073569 GSTIN: 27AABCA5790M1Z9