



**ASHA Resins Limited**

(Formerly known as Asha Resins Private Limited)

# ASHAFLOC - A95M

*Anionic Polyelectrolyte*

## DESCRIPTION

**ASHAFLOC - A95M** is an anionic, high molecular weight performance coagulant designed for solid-liquid separation processes. With 35% active content, it offers a high degree of efficiency in various applications. This product is highly effective as a filter aid, particularly in challenging situations where conventional filter aids fail.

**ASHAFLOC - A95M** is suitable for:

- Effluent water treatment.
- Removal of suspended particles from raw water.
- Oil-water emulsion separation.
- Low-turbidity water applications.

In most cases, it can be used alone or in combination with alum or inorganic flocculants for enhanced results.

## Recommended Dosage:

- **Coagulation Aid:** 0.25 ppm to 5 ppm.
- **Filtration Aid:** 10 ppm to 30 ppm.

## SPECIFICATIONS

Property	Details
Product Code	ASHAFLOC A-95M
Active Content	35%
Appearance	Highly viscous pourable liquid
Solubility	Fully water-soluble
Viscosity (CPS)	100-2000 cps

Regd. Office: Gat No 227/2, Village Dhanore,  
& Factory. Alandi-Markal Road, Tal. Khed  
Dist. Pune - 412 105  
CIN No: U99999MH1993PLC073569

Tel: 020-2638 2401  
E-mail: [office@asharesins.com](mailto:office@asharesins.com)  
Website: [www.asharesins.com](http://www.asharesins.com)  
GSTIN: 27AABCA5790M1Z9



# ASHA Resins Limited

(Formerly known as Asha Resins Private Limited)

Specific Gravity	1.01 – 1.06 (at 0.2%)
pH	8.5-10.0
Nature	Highly anionic

## DOSAGE

The required dosage depends on the solid content in the system to be treated:

- **Coagulation Aid:** 0.25 to 1.0 ppm.
- **Filter Aid:** 1 to 5 ppm.

## FEEDING

- Prepare a 0.2% solution in water.
- Ensure all solid particles are fully dissolved and no clumps ("fish eyes") remain.
- Recommended to dose at the system's inlet using a metering pump for optimal performance.

## HANDLING PRECAUTIONS

- **Safety:** Generally safe for handling.
- Avoid contact with eyes and prolonged skin exposure.
- Use protective gear if handling large volumes.

## PACKAGING

**ASHAFLOC - A95M** is available in **35 kg and 50 kg HDPE containers**.

## NOTE

The specifications provided are indicative and may be adjusted based on application needs.

Regd. Office: Gat No 227/2, Village Dhanore,  
& Factory. Alandi-Markal Road, Tal. Khed  
Dist. Pune - 412 105  
CIN No: U99999MH1993PLC073569

Tel: 020-2638 2401  
E-mail: [office@asharesins.com](mailto:office@asharesins.com)  
Website: [www.asharesins.com](http://www.asharesins.com)  
GSTIN: 27AABCA5790M1Z9



## **ASHA Resins Limited**

(Formerly known as Asha Resins Private Limited)

These suggestions and data are based on information we believe to be reliable and are offered in good faith. However, no guarantees are made, as conditions and methods of use are beyond our control. Users are advised to assess the material's suitability for their specific applications before commercial adoption.

For additional information, product samples, Material Safety Data Sheets (MSDS), or technical support, please contact us:

Regd. Office: Gat No 227/2, Village Dhanore,  
& Factory. Alandi-Markal Road, Tal. Khed  
Dist. Pune - 412 105  
CIN No: U99999MH1993PLC073569

Tel: 020-2638 2401  
E-mail: [office@asharesins.com](mailto:office@asharesins.com)  
Website: [www.asharesins.com](http://www.asharesins.com)  
GSTIN: 27AABCA5790M1Z9